

мм	2 R	F	S	w	Feature Name	Feature Description	APP	Plus Pack	Pro Pack	Target User	NCC Location	Note
•		~	~	~	sets	Handy tools to manage group(s) consisting with two or more Pro orgs that you own, including Monitor - Overview, Inventory, Change log and Configure - Settings, Org-to- Org VPN, and Administrators. Besides the Org-to-Org VPN which is used to manage cross-org VPN and its service, other settings share the same name features as Organization-wide but from the group perspective.			•	VAR&IT	Group-wide (appears if at least one group of organizations is created)	*Only NCC Admin owns more than 2 Pro orgs could create group.
•	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	logs	Every changes on your org. will be recorded so that you can check what settings have been made by whom and when.			•	VAR&IT	Organization-wide > Organization-wide manage > Change log	
	•	$\checkmark$	$\checkmark$	$\checkmark$	Login IP address ranges for an organization	List the IP addresses or ranges from which an administrator is allowed to log into the NCC.	(Follow NCC setting)		•	MSP	Organization-wide > Ogranization-wide manage > Organization settings	
•	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$		No limits on the number of admin (5 only on Base Pack).		8	•	MSP	Organization-wide > Administrators	
•		~	~	~		Allow unlimited authorized entries for the NCC cloud user database (50 only on Base Pack).		100		VAR&IT	Organization-wide > Organization-wide manage > Cloud authentication	
•				$\checkmark$	Users with VLAN	Support dynamic VLAN assignment on WPA2/3 enterprise authentication with Nebula cloud auth.			•		Organization-wide > Organization-wide manage > Cloud authentication (Account type: Users)	
•				~	Cloud Authentication DPPSK Account Type	Allow to create single or batch personal pre- shared key and send to applicant by email for wireless secure connection.			•	VAR&IT	Organization-wide > Configure > Cloud authentication (Account type: DPPSK)	
•		$\checkmark$	$\checkmark$	~	New site configuration clone	Replicate the configuration of an existing site instead of using the default settings while creating a new site.			•	VAR&II	<ol> <li>Site drop-down box &gt; + Create site</li> <li>Organization-wide &gt; Organization- wide manage &gt; Organization portal &gt; Create site</li> </ol>	
•				$\checkmark$	Configuration site based settings sync	Allows to easily propagate Site-wide general settings and AP SSID related configurations from one site to other sites under an org.			•	MSP	Organization-wide > Organization-wide manage > Configuration management	

1

۸ M2	R	F	S	W	Feature Name	Feature Description	APP	Plus Pack	Pro Pack	Target User	NCC Location	Note
•			~		Configuration switch settings clone	Clone switch device based settings from one device to others of the same model under an org.				MSP	Organization-wide > Organization- wide manage > Configuration management	
	~	$\checkmark$	~	$\checkmark$	Configuration backup/restore	Backup and restore your settings of your sites and switch devices.			•	VAR&IT	Organization-wide > Organization- wide manage > Configuration management	
			~	~	Configuration template*	Allow many sites to be deployed and keep updated following a single base configuration template.				MSP	Organization-wide > Organization- wide manage > Configuration templates	*Currently Security Appliance & Mobile Router configuration have not yet supported.
•		$\checkmark$	$\checkmark$	$\checkmark$	Add client- blocklist/whitelist	Define client MAC/IP (MAC for AP&SW, IP for GW) filtering/block list or whitelist/bypass the captive portal of a SSID or VLAN in advance.			•	VAR&IT	Site-wide > Clients	
•		$\checkmark$		$\checkmark$	Connection log (former name Client Diagnostics)	New tab page of Clients that aims to provide friendly and end-to-end complete connection journey based logs to help administrators easily pinpoint client's connection issues				VAR&IT	Site-wide > Clients > Connection log	
•				~		The latest tab page of Clients that aims to provide adminstrators a comprehesive dashboard and reports of WiFi client's connection issues			•	VAR&IT	Site-wide > Clients > WiFi Aid Site-wide > Monitor > Access points > WiFi Aid	
	$\checkmark$	V	V	~	Site-wide topology	<ol> <li>Auto illustrates the network topology including Zyxel non-Nebula devices.</li> <li>Help remote trouble shooting by showing device and link info. &amp; status.</li> <li>Automatic visual topology for Smart mesh.</li> <li>Device supports "Reboot" action.</li> <li>Switch PoE link supports "power cycle" action</li> </ol>		•		VAR&IT	Site-wide > Topology	
•		~	~		Summary report email & schedule	Send out site or device statistics, with logo options, by email now or by schedule.		•	•	MSP	Site-wide > Summary report Site-wide > Monitor > Access points / Switches / Firewall > Summary report	
•		$\checkmark$	~	$\checkmark$	Custom range up to 365 days on summary report	View up to 365 days statistics including site- wide, AP, SW, GW summary report (24 HR only on Base Pack).		7D		VAR&IT	Site-wide > Summary report Site-wide > Monitor > Access points / Switches / Firewall > Summary report	
•		$\checkmark$	$\checkmark$	$\checkmark$		View device usage chart up to 365 days (24 HR only on Base Pack).		7D	•	VAR&IT	Site-wide > Devices > Access points / Switches / Firewall > [Select AP / SW ]	
•		$\checkmark$	$\checkmark$	$\checkmark$	365 days statistics on client monitoring	View client traffic chart up to 365 days (24 HR only on Base Pack).		7D		VAR&IT	Site-wide > Clients > [Select client]	

M M	2 R	F	S	W	Feature Name	Feature Description	APP	Plus Pack	Pro Pack	Target User	NCC Location	Note
		~	~	~	365 days statistics on device event log access	View event log chart up to 365 days (24HR only on Base Pack).		7D	•	VAR&IT	Site-wide > Monitor > Access points / Switches / Firewall > Event log	
		$\checkmark$	$\checkmark$	$\checkmark$	Export data to CSV/XML file	Download the data currently displayed in the table of eg. Inventory, Cloud authentication etc. in either a CSV or XML file format.			•	VAR&IT	All monitoring pages with table data	
		$\checkmark$	~	$\checkmark$	Open API	Open API for Ecosystem Partner Application Integration				MSP	Monitoring and a bit basic configuration related (keep updating, please check with PLM/AE for more details)	
		$\checkmark$	$\checkmark$	$\checkmark$	DPPSK API access	Support to generate an API token (DPPSK third-party integration for now).			•	MSP	Site-wide > Configure > Site settings	
	~	~	~	V	Smart email alerts	NCC integrates & intelligently scans at configuration changes, network topology, device status and security service events to send smart email alerts when necessary.		•		VAR&IT	Site-wide > Configure > Alert settings	
					Firmware upgrade schedules on a per- device basis	On top of scheduling site-wide firmware upgrade, you're also able to assign specific firmware upgrade time on particular (can be filtered and selected by tag, model, current version etc.) device.		•	•		Site-wide > Configure > Firmware Management	
	• •	~	~	V	Org-wide firmware upgrade	User can upgrade device's firmware across multiple sites. The Firmware Upgrades allows organization admins to manage firmware versions on a per-site and per-device type basis.		•		VAR&IT	Organization-wide > Organization- wide manage > Firmware management	
	$\checkmark$	$\checkmark$	$\checkmark$	$\checkmark$	Priority support reques (direct NCC )	tSend us support ticket directly from NCC UI and Nebula mobile APP and get case updates.	•		•	VAR&IT	Help > Support request	
	<ul> <li>✓</li> </ul>	$\checkmark$	$\checkmark$	$\checkmark$	Web chat support (direct NCC)	Web chat with tech support directly from NCC UI.			•	VAR&IT	All website	
	√	$\checkmark$	$\checkmark$	$\checkmark$	Upload photo from Gallery	Upload up to 5 photos to NCC from phone's photo Gallery (1 photo only on Base and Plus Pack).	•		•		Site-wide > Devices (eg.Access points) > Access points > [Select AP] Photo	

M M2

 $\bullet$ 

M M2 R	F	s v	/ Feature Name	Feature Description	APP	Plus Pack	Pro Pack	Target User	NCC Location	Note
• •	√ ,	/ •	Remote CLI access / Configurator	Provide remote CLI access live tools to AP, Switch and Security Appliance and remote Web GUI access live tools to Mobile Router			•	VAR&IT	Site-wide > Devices > Access point / Switches / Firewall > [Select AP / SW / FW ] Live tools	
		v	Wireless health monitor and report	Provide administrators with a health condition overview of their wireless networks, per AP and per client, and quickly take actions to improve poor performance or user experience.			•	VAR&IT	Site-wide > Monitor > Access points > Wireless health	
		v	Per AP (room) per <pre>     SSID </pre>	Allow to set up programmable SSID & PSK for each AP			•	VAR&IT	Site-wide > Configure > Access points > SSID settings	
		v	Dynamic Personal Pre-Shared Key (DPPSK)	Allow the authentication of users with individual unique key to the wireless network. And also allow to use DPPSK as 2-Factor Auth. for IOT devices by email.			•	VAR&IT	Site-wide > Configure > Access points > SSID advanced settings	
•		v	Voucher	Allow the authentication of users to the wireless network by sign-in with voucher code		•		VAR&IT	Site-wide > Monitor > Access points > Vouchers	
		v	Captive Portal MAC Auth. Fallback	To provide a better user experience, avoid captive portal with RADIUS re-authentication by falling back to MAC authentication when clients rejoin the network			•	MSP	Site-wide > Configure > Access points > SSID advanced settings	
		v	RADIUS NAS ID customizable	Allow to set a NAS identifier to be used to identify location/Nebula site while integrating with an external captive portal service with RADIUS authentication.			•	MSP	Site-wide > Configure > Access points > SSID advanced settings	
		٧	RADIUS accounting for captive portal	Enable to configure Radius accounting server settings for captive portal with RADIUS authentication.			•	MSP	Site-wide> Configure > Access points > SSID advanced settings	

17.10

M2 R F S	w	Feature Name	Feature Description	APP	Plus Pack	Pro Pack	Target User	NCC Location	Note
	~		Allow to customize the parameter sent to third party captive portal integration.			•	MSP	Site-wide> Configure > Access points > Captive portal customization	
	~		Granularity control of the RSSI threshold settings per AP, for a more accurate deployment.			•	VAR&IT	Site-wide > Configure > Access points > Radio settings > [Edit the Selected AP]	
	~		Provide traffic shaping (rate-limit) to user/user group by assigning to different VLAN(s)			•	VAR&IT	Site-wide > Configure > Access points > Traffic shaping	Support model: NWA1123ACv3, WAC500, WAC500H, NWA110AX, NWA210AX, WAX510D, WAX610D, WAX630S, WAX650S
•	$\checkmark$		Allow to export the traffic log of the AP to a syslog server in NAT mode			•	VAR&IT	Site-wide > Configure > Site settings	
V			Provide utilization, network analysis including UPnP packet detection and client statistics of the multicast groups or channels in an IPTV environment, allowing to import channel list in advance.			•	MSP	Site-wide > Monitor > Switches > IPTV report	
~			Set IGMP snooping advanced settings such as role, mode, timers, unknown multi-cast drop per VLAN and IPTV topology setup for an effective bandwidth utilization design in an IPTV environment.			•	MSP	Site-wide > Configure > Switches > Advanced IGMP	
V		Monitoring with ONVIF	Provide the advanced deployment and maintenance page for the powered devices, ex. IP camera including ONVIF IPCAM discovery.			•	VAR&IT	Site-wide > Monitor > Switches > Surveillance	G\$1350 series only for now
$\checkmark$		Auto PD Recovery	Auto recover malfunctioning PD by taking advantage of their PoE dependency		٠		VAR&IT	Site-wide > Configure > Switches > Switch ports > [Select Port]	Supporting GS1350 & GS2220 series
V			Allow to allocate network devices from different vendors into different VLANs for easy management and traffic priority.		•		VAR&IT	Site-wide > Configure > Switches > Switch settings	
$\checkmark$			Protect network access from illegal IP addressing configured by DHCP and/or manual/static setting			•	VAR&IT	Site-wide > Configure > Switches > Switch settings	
V			Support Layer 3 function to create IP interface and IPv4 static route			•	VAR&IT	Site-wide > Configure > Switches > IP & Routing	

17.10

M M2 R	F S W	Feature Name	Feature Description	APP	Plus Pack	Pro Pack	Target User	NCC Location	Note
	~		Experience high-performance network management by managing multiple switches as a single entity, simplifying maintenance while increasing scalability.			•		Site-wide > Configure > Switches > Stacking management	
•	V		View Anti-virus/Application Patrol/Content Filtering/ Intrusion Detection and Prevention usage & hits of the network clients at the network level and per client level (24HR only on Base Pack).		7D	365D	MSP	Site-wide > Monitor > Security gateway > NSS analysis report	Requires NSG NSS-SP license to see the report
•	$\checkmark$		Collecting and archiving traffic log from Nebula security appliance. Customer can download archived traffic log from SecuReporter.			•	VAR&IT	Site-wide > Monitor > Firewall > SecuReporter	
	~	VPN topology with traffic usage	Provide visualize virtual private network connections & usage (per tunnel) between different sites of VPN networks (areas)			•	VAR&IT	Organization-wide > Organization-wide manage > VPN Orchestrator	
	$\checkmark$		Smart VPN configuration includes software- defined design to easily build scalable VPN networks (areas) and setup non-Nebula VPN peers among HQ and branches			•	VAR&IT	Organization-wide > Organization-wide manage > VPN Orchestrator	
	~	VPN provision script email	Send L2TP Client provisioning scrip by email for client VPN's quick setting			•	VAR&IT	Site-wide > Configure > Security gateway / Firewall > Remote access VPN (L2TP over IPSec VPN Server)	
	$\checkmark$ $\checkmark$	Detection &	Support automatically block/quarantine clients based on the USG Flex UTM Security Pack's CDR policy.			•	VAR&IT	Site-wide > Configure > Collaborative detection & response	Requires USG Flex UTM Security Pack license to do CDR management

M= Management Feature (NCC); M2= (Sub.) Management Property; R= 5G/4G Mobile Router Feature; F= Firewall Feature; S= Switch Feature; W= Wireless Feature